

VRLA Rechargeable Battery

HRL5.8-12



Measures Technology Values Innovation

FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high rate usage
- Absorbent Glass Mat technology for efficient gas recombination
- The power density at 5 min~15min discharging rate is 30% higher than BP series


APPLICATIONS

- UPS
- Data Centre
- Power Packs
- Wind Power
- Jump Starter
- Medical Equipments
- Laboratory Equipment



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	5.3Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	1880g(4.15lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	≤23mΩ (Fully Charged)
Max. Discharge Current	79.5 A (5 sec.)
Max. Charge Current	1.59 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL94 HB) HRL5.8-12 Optional: Flame Retardant ABS(UL94 V-0) HRL5.8-12FR



MH19884



- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)

OUTER DIMENSIONS

TERMINAL TYPE

Length

90±1.5 (3.54±0.06)

Width


70±1.5 (2.76±0.06)

Container Height


102±1.5 (4.02±0.06)

Total Height


106±2.0 (4.17±0.08)



Terminal T1



Terminal T2



Constant power discharge characteristics at 25 °C/77 °F

Unit: W

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	237.8	162.4	117.6	100.3	76.3	58.0	48.5	42.7	23.5
1.70V	284.2	181.3	127.9	106.3	79.5	60.2	50.0	43.6	24.0
1.60V	304.5	190.7	133.7	110.2	81.2	61.6	51.0	44.4	24.4
1.50V	313.2	194.3	136.6	111.9	82.2	62.4	51.6	44.8	24.5
1.40V	319.0	196.9	138.2	113.0	82.8	62.8	52.1	45.1	24.6
1.30V	321.9	198.7	139.2	113.7	83.3	63.1	52.3	45.2	24.6

Constant current discharge characteristics at 25 °C/77 °F

Unit: A

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	21.23	14.24	10.17	8.61	6.46	4.88	4.05	3.55	1.96
1.70V	25.83	15.90	11.07	9.11	6.73	5.06	4.19	3.63	2.00
1.60V	27.68	16.73	11.57	9.45	6.88	5.18	4.27	3.70	2.03
1.50V	28.47	17.04	11.82	9.60	6.97	5.24	4.32	3.73	2.04
1.40V	29.00	17.28	11.95	9.69	7.02	5.28	4.36	3.76	2.05
1.30V	29.26	17.43	12.04	9.75	7.06	5.31	4.38	3.77	2.05

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.